

TELESCOPIC RANGE SCALISSIMA®

Scalissima Plus



VIDEO

Telescopic top quality ribbed aluminium 3-in-1 ladder with large base especially designed for heavy duty use. It has reinforced profiles for better resistance to meet European Standards up to 12 rungs. It can be used as a stepladder, lean-to wall ladder and on stairs.



n.	m	m	m	cm	Kg
8+8	1,22	1,91	4,01	63	12,0
10+10R	1,50	2,44	5,15	63	14,2
12+12R	1,78	2,94	6,25	75	17,5

REINFORCED PROFILES
ALL MODELS ARE TESTED ACCORDING TO EN131



Lean-to wall

- Non-skid flanged rungs 27x27 mm
- Aluminium hinge knobs
- Steel safety blocking hooks covered in nylon
- Distance between rungs 28 cm
- Inner profile 63x27 mm
- Outer profile 70x31 mm
- Inner ramp width 36,5 cm
- Non-skid reinforced rubber feet
- Thermo-shrinkable plastic package with showcard

Models (R)

NEW HINGES

Quick positioning of the hinges allows:

- opening and closing as a step-ladder without modifying hinge position
- blocking ladder when used as a stepladder modifying hinge position
- opening/closing the ladder for use against walls by modifying hinge position

Aluminum lamellar hinge for the highest models - 10 years guarantee

On request:

- Stabiliser (SALLARUS1 mm 1132)
- Foldable stabiliser
- Note: Scalissima is not prepared for the assembling of the stabilizer. The customer can choose whether to prepare autonomously the ladder or have it prepared by Svelt
- Wheels kit
- Safety 60 cm guardrail and platform kit
- Safety 100 cm guardrail and platform kit



Steel safety blocking hooks covered in nylon



Used on stairs



optional

Stabilizer



optional

Wheels kit

